

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission with Ball Hitch										
Model	(LU3) Vortec 4.3L V6 MFI		(LY2) Vortec 4.8L V8 Gas SFI		(LY5/LH6) Vortec 5.3L V8 gas SFI		(LMG) Vortec 5.3L V8 SFI FlexFuel		(L76) Vortec 6.0L V8 SFI	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
CC10703	3.23	4800 (2177)	3.23	5200 (2359)	3.42	7200 (3266)	3.42	7200 (3266)		
	3.73	5300 (2404)	3.73	7200 (3266)	3.73	8200 (3720)	3.73	8200 (3720)		
CC10903	3.23	4700 (2132)	3.23	5100 (2313)	3.42	7000 (3175)	3.42	7000 (3175)		
	3.73	5200 (2359)	3.73	7100 (3221)	3.73	8000 (3629)	3.73	8000 (3629)		
CK10703	3.73	5100 (2313)	3.42	5900 (2676)	3.73	7900 (3583)	3.73	7900 (3583)		
			4.10	7900 (3583)	4.10	8900 (4037)	4.10	8900 (4037)		
CK10903	3.73	4900 (2223)	3.42	5900 (2676)	3.73	7900 (3583)	3.73	7900 (3583)		
			4.10	7900 (3583)	4.10	8900 (4037)	4.10	8900 (4037)		
CC10753	3.23	4300 (1950)	3.23	4700 (2132)	3.42	6700 (3039)	3.42	6700 (3039)		
	3.73	4800 (2177)	3.73	6700 (3039)	3.73	7700 (3493)	3.73	7700 (3493)		
CC10753 w/o (NHT)									3.73	8800 (3992)
CC10753 w/(NHT)									3.73	10200 (4627)
CC10953					3.42	6500 (2948)	3.42	6600 (2994)		
					3.73	7500 (3402)	3.73	7600 (3447)		
CK10753			3.42	5500 (2495)	3.73	7500 (3402)	3.73	7500 (3402)		
			4.10	7500 (3402)	4.10	8500 (3856)	4.10	8500 (3856)		
CK10753 w/o (NHT)									3.73	8500 (3856)
CK10753									4.10	10500

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission with Ball Hitch										
Model	(LU3) Vortec 4.3L V6 MFI		(LY2) Vortec 4.8L V8 Gas SFI		(LY5/LH6) Vortec 5.3L V8 gas SFI		(LMG) Vortec 5.3L V8 SFI FlexFuel		(L76) Vortec 6.0L V8 SFI	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
w/(NHT)										(4763)
CK10953					3.73	7300 (3311)	3.73	7400 (3357)		
					4.10	8300 (3765)	4.10	8400 (3810)		
CC10553	3.23	4400 (1996)	3.23	4800 (2177)	3.42	6800 (3084)	3.42	6800 (3084)	3.73	8900 (4037)
	3.73	4900 (2223)	3.73	6800 (3084)	3.73	7800 (3538)	3.73	7800 (3538)		
CK10553			3.42	5500 (2495)	3.73	7500 (3402)	3.73	7500 (3402)	3.73	8600 (3901)
			3.73	7500 (3402)	4.10	8500 (3856)	4.10	8500 (3856)		
CC10543			3.23	4600 (2087)	3.42	6600 (2994)	3.42	6600 (2994)		
			3.73	6600 (2994)	3.73	7600 (3447)	3.73	7600 (3447)		
CC10543 w/o (NHT)									3.73	8700 (3946)
CC10543 w/(NHT)									3.73	10200 (4627)
CK10543			3.42	5400 (2449)	3.73	7500 (3402)				
			4.10	7400 (3357)	4.10	8500 (3856)				
CK10543 w/o (NHT)									3.73	8400 (3810)
CK10543 w/(NHT)									4.10	10500 (4763)

Silverado 1500 models are limited to 5000 lb. trailer rating unless equipped with (Z85) Handling/Trailering Suspension Package or (Z60) High-Performance Suspension Package or (Z71) Off-Road Suspension Package.

Addition of trailer tongue weight cannot cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGVWR) of Gross Vehicle Weight Rating (GVWR).

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission with Ball Hitch										
Model	(LU3) Vortec 4.3L V6 MFI		(LY2) Vortec 4.8L V8 Gas SFI		(LY5/LH6) Vortec 5.3L V8 gas SFI		(LMG) Vortec 5.3L V8 SFI FlexFuel		(L76) Vortec 6.0L V8 SFI	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)

(Z82) Trailering Equipment, heavy-duty includes trailer hitch platform, trailer electrical connector and suspension upgrade if necessary.

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission								
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)							
	9500 (4309)	10000 (4536)	11000 (4990)	12000 (5443)	13000 (5897)	14000 (6350)	15500 (7031)	16000 (7258)
(LU3) Vortec 4.3L V6 MFI	3.23	3.73						
(LY2) Vortec 4.8L V8 Gas SFI		3.23	3.42	3.73	4.10			
(LY5/LH6) Vortec 5.3L V8 gas SFI				3.42	3.73	4.10		
(LMG) Vortec 5.3L V8 SFI FlexFuel				3.42	3.73	4.10		
(L76) Vortec 6.0L V8 SFI						3.73 ¹	3.73 ²	4.10 ³

1 - Not available with (NHT) Max Trailering Pack.

2 - Requires 2WD Models and (NHT) Max Trailering Pack.

3 - Requires 4WD Models and (NHT) Max Trailering Pack.

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 15 to 25% of the trailer weight is the recommended 5th Wheel or Gooseneck kingpin load.

Automatic with 5th Wheel or Gooseneck Hitch						
Model	(LY2) Vortec 4.8L V8 Gas SFI		(LY5/LH6) Vortec 5.3L V8 gas SFI		(L76) Vortec 6.0L V8 SFI	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
CC10703	3.73	7200 (3266)	3.73	8200 (3720)		
CC10903	3.73	7000 (3175)	3.73	8000 (3629)		
CK10703	4.10	7300 (3311)	4.10	8300 (3765)		
CK10903	4.10	7800 (3538)	4.10	8800 (3992)		
CC10753	3.73	6700 (3039)	3.73	7700 (3493)	3.73	8700 (3946)
CC10753 w/(NHT)					3.73	10100 (4581)
CC10953			3.73	7500 (3402)		
CK10753	4.10	7500 (3402)	4.10	8500 (3856)	3.73	8500 (3856)
CK10753 w/(NHT)					4.10	10400 (4717)
CK10953			4.10	8300 (3765)		