

Size	Single/ Dual	Tire Load Limits (lbs.) at Various Inflation Pressures (PSI)									
		35	40	45	50	55	60	65	70	75	80
LT345/55R17	Single	2270	2410	2620	2835 (D) 117						
LT355/70R17	Dual	2755	2790	2850	2910 (D) 118						
LT355/70R17	Single	3000	3065	3130	3195 (D) 121						
LT205/60R18	Dual	1080	1185	1285	1390	1480	1570	1655 (D) 98			
LT205/60R18	Single	1185	1300	1410	1520	1625	1725	1820 (D) 101			
LT245/70R18	Dual	1595	1745	1895	2040	2185	2325	2470	2590	2715	2835 (E) 117
LT245/70R18	Single	1750	1920	2085	2270	2400	2555	2680	2845	2985	3085 (E) 120
LT255/55R18	Dual	1330	1460	1590	1710	1825	1945	2040 (D) 105			
LT255/55R18	Single	1460	1605	1745	1875	2005	2135	2270 (D) 109			
LT255/65R18	Dual	1585	1740	1885	2040	2170	2305	2470	2570	2700	2835 (E) 117
LT255/65R18	Single	1740	1910	2070	2270	2385	2535	2680	2825	2965	3085 (E) 120
LT255/70R18	Dual	1690	1850	2010	2205	2315	2460	2600 (D) 114			
LT255/70R18	Single	1855	2035	2210	2405	2545	2705	2835 (D) 117			
LT265/60R18	Dual	1540	1695	1845	1985	2120	2250	2335	2505	2635	2755 (E) 116
LT265/60R18	Single	1695	1865	2025	2205	2330	2475	2600	2755	2895	3000 (E) 119
LT265/65R18	Dual	1665	1830	1985	2205	2285	2430	2600	2705	2840	3000 (E) 119
LT265/65R18	Single	1830	2010	2180	2405	2510	2670	2835	2970	3120	3305 (E) 122
LT265/70R18	Dual	1785	1960	2130	2335	2450	2605	2835	2900	3045	3195 (E) 121
LT265/70R18	Single	1960	2155	2340	2535	2690	2860	3085	3185	3345	3525 (E) 124
LT275/65R18	Dual	1765	1940	2100	2335 (C) 110	2420	2570	2755	2865	3010	3085 (E) 120
LT275/65R18	Single	1940	2130	2310	2535 (C) 113	2660	2825	3000	3150	3305	3415 (E) 123
LT275/70R18	Dual	1885	2065	2250	2470 (C) 112	2585	2750	2910	3060	3210	3305 (E) 122
LT275/70R18	Single	2070	2270	2470	2680 (C) 115	2840	3020	3195	3360	3530	3640 (E) 125
LT285/60R18	Dual	1715	1885	2050	2270	2350	2505	2680 (D) 115	2785	2925	3000 (E) 119
LT285/60R18	Single	1885	2070	2250	2470	2585	2750	2910 (D) 118	3060	3215	3305 (E) 122
LT285/65R18	Dual	1850	2035	2205	2335	2540	2700	2910 (D) 118	3010	3160	3305 (E) 122
LT285/65R18	Single	2035	2235	2425	2600	2790	2965	3195 (D) 121	3305	3470	3640 (E) 125
LT285/70R18	Dual	1985	2180	2365	2600	2725	2895	3085	3225	3385	3525 (E) 124
LT285/70R18	Single	2180	2395	2600	2835	2995	3180	3415	3545	3720	3860 (E) 127
LT285/75R18	Dual	2085	2290	2485	2755	2860	3040	3195	3385	3555	3750 (E) 126
LT285/75R18	Single	2290	2515	2730	3000	3145	3340	3525	3720	3905	4080 (E) 129
LT295/65R18	Dual	1955	2150	2330	2535	2680	2850	3000	3175	3330	3525 (E) 124
LT295/65R18	Single	2150	2360	2560	2755	2945	3130	3305	3490	3660	3860 (E) 127
LT295/70R18	Dual	2090	2295	2490	2755	2865	3045	3195	3395	3560	3750 (E) 126
LT295/70R18	Single	2295	2520	2735	3000	3150	3345	3525	3730	3910	4080 (E) 129
LT305/60R18	Dual	1930	2080	2255	2470	2600	2760	2910 (E) 118			
LT305/60R18	Single	2150	2285	2480	2680	2855	3035	3195 (E) 121			
LT305/65R18	Dual	2150	2250	2440	2680	2805	2985	3195 (E) 121			
LT305/65R18	Single	2335	2470	2680	2910	3085	3280	3525 (E) 124			
LT305/70R18	Dual	2270	2405	2615	2835	3010	3200	3415 (E) 123			
LT305/70R18	Single	2470	2645	2875	3085	3310	3515	3750 (E) 126			
LT305/75R18	Dual	2335	2530	2750	3000 (D) 119	3160	3360	3640 (E) 125			
LT305/75R18	Single	2600	2780	3020	3305 (D) 122	3475	3695	3970 (E) 128			
LT315/70R18	Dual	2335	2530	2745	3000	3160	3360	3525 (E) 124			
LT315/70R18	Single	2600	2780	3015	3305	3470	3690	3860 (E) 127			
LT325/60R18	Dual	2150	2285	2480	2755	2855	3035	3195 (E) 121			
LT325/60R18	Single	2335	2510	2725	3000	3135	3335	3525 (E) 124			
LT325/65R18	Dual	2335	2470	2680	2910 (D) 118	3085	3280	3525 (E) 124			
LT325/65R18	Single	2535	2715	2945	3195 (D) 121	3390	3605	3860 (E) 127			
LT345/60R18	Single	2535	2745	2980	3195 (D) 121						
LT355/65R18	Single	2910	3110	3375	3640	3750	3860	3970 (E) 128			
LT375/50R18	Dual	2150	2300	2500	2755	2875	3055	3195 (E) 121			
LT375/50R18	Single	2335	2530	2745	3000	3160	3355	3525 (E) 124			
LT375/60R18	Dual	2680	2830	3070	3305 (D) 122						
LT375/60R18	Single	2910	3110	3375	3640 (D) 125						